



BROCK LATCH-LOCK® WALK-THROUGH DOOR

SAFETY FIRST

The one-piece outer door swings back out of the way and latches securely against the side of the bin. The interlocking panel system of the inner door carries a U.S. patent with your safety being uppermost in the design. The bottom panel cannot be opened before the top panels to avoid a sudden or damaging discharge of grain. And because panel latches must be secured from the outside, you cannot be accidentally locked inside the bin.

EASY ACCESS

Each panel is opened using one hand to simply lift the latch and swing the panel into the bin. No wrenches or special tools are required.

STRENGTH WHERE IT COUNTS

With the inner door secured, the panels become an integral part of the structural unit, providing added strength across the door frame to accommodate various grain loads.

MORE DOOR FOR THE MONEY

1. Splash guard on door header effectively channels rain water away from the opening.
2. Since panels must be manually closed from outside, they cannot accidentally shut, even in a strong wind.
3. Inter-locking panels provide safety and convenience by opening only in proper sequence.
4. Special retaining pins carry hoop tension across the door opening for added security.
5. High-strength steel door frame assures proper alignment year after year.
6. An outside step below the door is standard with all door models.
7. An inside step below the door is standard with all heavy latch bar door models.



Brock LATCH-LOCK® Walk-Through Door Specifications

DOOR DESCRIPTION*†	DOOR OPENING DIMENSIONS		BIN DIAMETER	
	INCHES	MM	FEET	METERS
Latch Bar Door #1 & #2	26 x 61.5	660 x 1562	15 to 48	4.6 to 14.6
Latch Bar Door #3	26 x 61.5	660 x 1562	24 to 60	7.3 to 18.3
Latch Bar Door #3 with Tie Bars	26 x 61.5	660 x 1562	30 to 78	9.1 to 23.8
Heavy Latch Bar Doors #4, #5 & #6**	26 x 56	660 x 1422	42 to 105	12.8 to 32

* Latch Bar Doors are not available for use in a bin with three inside stiffeners per sheet.

** Option of paint or galvanized steel finish.

† Door model required is determined by bin height.

NOTE: A walk-through LATCH-LOCK® Door is standard on all BROCK® farm and stiffened farm bins and optional on most BROCK commercial bins. A 1-ring (tier) LATCH-LOCK Door is available for all farm and commercial grain bins.



Brock Grain Systems
Chore-Time Brock International
Divisions of CTB, Inc.

Milford, IN • Kansas City, MO • Frankfort, IN
Phone: 574.658-4191 or 574.658.9323 (International)
Internet: www.brockmfg.com or www.ctbworld.com
E-Mail: brock@brockmfg.com